



USER GUIDE

COMPETITION ILLUMINATED RETICLE

COMPETITION RETICLE

The COMPETITION Reticle is designed to compensate for the trajectory of a specific ammunition.

Please note that the reticle is based upon ballistic information and may or may not produce these exact results based on a variety of variables such as:

- Actual Velocity (Ammunition manufacturers' information may not match the exact velocity out of your firearm. The best way to confirm velocity is to use a chronograph).
- Temperature
- Humidity
- Altitude
- Barometric Pressure · Condition of firearm · Scope mounting system 0.50 MOA DOT

8.96



Get precise bullet drops for your reticle and ammunition. Use our FREE Crimson Trace® Ballistic Calculator. *Available for all Crimson Trace® Reticles

Crimson Trace® Ballistic Calculator
Go to www.crimsontrace.com
for more information.



Subtensions for yardages were calculated using the following variables. Note: all subtensions are calculated at MAX magnification.

- Caliber .223
- Muzzle Velocity (fps) 3165
- Bullet Wt (gn) 55
- Ballistic Coefficient G1 0.246
- Zero Range (vd) 100
- Temp (Fahrenheit) 59
- Altitude (feet) 2500
- · Scope Height over bore (in) 2.50

SUBTENSION	YARDS	MOA
Α	200	0.99"
В	300	3.28"
С	400	6.38"
D	500	10.38"
E	600	15.51"



CRIMSON TRACE HEADQUARTERS
9780 SW FREEMAN DRIVE, WILSONVILLE, OR 97070
TELEPHONE: 800-442-2406 • FAX: 503-783-5334
CRIMSONTRACE.COM