


The NEW PRECISION RIFLE SCOPES



MODEL

NEW | Vudu 3.5-18x50SFP

BLACK



REV2 FOV

The new Vudu 3.5-18x Second Focal Plane scope is the ideal scope for medium- and long-range shooting. It features EOTECH's XC™ High-Density glass, rugged 34 mm tube and easy-to-use tactical turrets equipped with covers to prevent inadvertent adjustments. Other features include a side-mounted parallax adjustment, illuminated reticle and removable throw lever for quick magnification adjustments.

- Second Focal Plane
- Objective Lens Diameter — 50 mm
- Single-Piece 34 mm tube
- Sunshade included
- Illuminated Reticle
- XC High-Density Glass
- Parallax Adjustment
- Tactical Turrets w/ EZ Chek™ Zero Stop
- .25 MOA or .1 MRAD Adjustments
- MSRP \$1,499



Parallax Adjustment




Part No.	Overall Length	Weight w/batteries	Actual Magnification	Exit Pupil	Eye Relief	Actual Field-Of-View	Field-Of-View (@ 100 Yards)	Battery Type	Battery Life (At Room Temp.)	Battery Life (At Auto Shut-off)
VDU3-18SFHC1	377 mm (14.843 in.)	878 g (30.97 oz)	3.5x - 18x	3.5x: 10.9 mm (.43 in.); 18x: 2.8 mm (.11 in.)	1x: 86-100 mm; (3.39-4.02 in.); 18x: 88-99 mm (3.46-3.90 in.)	3.5x: 5.77 degrees; 18x: 1.12 degrees	3.5x: 9.2 m (30.2 ft.); 18x: 1.8 m (5.9 ft.)	CR2032	Approx. 500 hrs.	Approx. 2 hrs.

MODEL

NEW | Vudu 8-32x50SFP

BLACK



REV1 FOV

EOTECH's new 8-32x50 mm Vudu scope is ideal for competitive and recreational long range shooting. It features competitive turrets with easy-to-read minute of angle adjustments. The turrets are calibrated in .125 MOA (1/8" per click) offering extreme precision and accuracy. A side-mounted parallax adjustment allows you to focus the reticle to the target and the XC High-Density glass provides great detail at extreme distances.

- Second Focal Plane
- Objective Lens Diameter — 50 mm
- Single-Piece 34 mm tube
- XC High-Density Glass
- Parallax Adjustment
- Competition Tactical Turrets
- .125 MOA Adjustments
- Sunshade included
- MSRP \$1,699



Covered, competition turrets



Part No.	Overall Length	Weight w/batteries	Actual Magnification	Exit Pupil	Eye Relief	Actual Field-Of-View	Field-Of-View (@ 100 Yards)	Battery Type	Battery Life (At Room Temp.)	Battery Life (At Auto Shut-off)
VDU8-32SFHC	385 mm (15.16 in.)	926 g (32.66 oz)	8x - 32x	8x: 5.3 mm (.21 in.); 32x: 1.6 mm (.06 in.)	8x: 86-98 mm; (3.39-3.86 in.); 32x: 89-98 mm (3.50-3.86 in.)	8x: 2.53 degrees; 32x: 0.63 degrees	8x: 4.0 m (13.2 ft.); 32x: 1.0 m (3.3 ft.)	CR2032	Approx. 500 hrs.	Approx. 2 hrs.

MODEL

NEW | Cantilever Mount

BLACK

EOTECH's new Cantilever Mount is a perfect solution for modern sporting rifles. Offered in both 30 mm and 34 mm, and machined out of aircraft-grade aluminum, the Cantilever Mount includes an adjustable, locking quick-detach lever for easy attachment and removal. Designed to fit both 1" Weaver and MIL-STD 1913 rails and a height-above-rail of 37mm, this mount includes a 2-inch offset that positions the scope in a forward position, providing the correct eye relief and cheek placement for most AR15/AR10 platforms. Made in USA. **MSRP \$195**

Part No.

MN2015 - PRS 2" Cantilever Mount - 30 mm

MN2016 - PRS 2" Cantilever Mount - 34 mm



MODEL

NEW | 2-Piece Ring Mounts

BLACK

A great way to compliment your new rifle scope is with EOTECH's high-quality 2-Piece Ring Mounts. Precision CNC machined out of aircraft grade aluminum, these mounts are offered in low (21 mm), medium (25 mm), high (30 mm) and ultra-high (37 mm). Sold (2) rings per package. Hex wrench included. Made in USA. **MSRP \$65**

Ultra-High
Ring Mount
(37 mm)High
Ring Mount
(30 mm)Medium
Ring Mount
(25 mm)Low
Ring Mount
(21 mm)

Part No.

MN2007 - PRS Ring Mount - 30 mm x 21 mm (Low)

MN2008 - PRS Ring Mount - 30 mm x 25 mm (Med)

MN2009 - PRS Ring Mount - 30 mm x 30 mm (High)

MN2010 - PRS Ring Mount - 30 mm x 37 mm (Ultra-High)

Part No.

MN2011 - PRS Ring Mount - 34 mm x 21 mm (Low)

MN2012 - PRS Ring Mount - 34 mm x 25 mm (Med)

MN2013 - PRS Ring Mount - 34 mm x 30 mm (High)

MN2014 - PRS Ring Mount - 34 mm x 37 mm (Ultra-High)

The Cantilever Mount and 2-Piece Ring Mounts are controlled under the Export Administration Regulations (EAR) and may not be exported without proper authorization by the U.S. Department of Commerce.

*These are preliminary specifications. EOTECH reserves the right to change the product specifications at any time without notice. All brand names, product names referenced are trademarks, registered trademarks or trade names of their respective holders.