RAPIDSTRIKE

RED DOT



Red Dot	
Reticle Type	3 MOA dot
Reticle Color	Red
Reticle Brightness	9 (7 day - 2 NV)
Illuminated Reticle (yes/no)	Yes
Magnification	1x
Eye Relief (in/mm)	Unlimited
Objective Lens Diameter (mm)	21
MOA Adjustment (one click)	1 MOA
Footprint	Aimpoint T2
Parallax Setting (yds)	100
Windage/Elevation Adjustment Range	120 MOA
Shake Awake	Yes
Shake Awake Timing (min)	15
Parallax Setting (yrds)	100
Operating Temperature	-4 to 131°F / -20 to 55 °C
Battery Type	CR2032
Body Material	Aluminum 6061-T6
Dimensions with High Mount (in/mm)	2.72 x 1.42 x 2.5 69 x 36 x 64
Dimensions of Sight Only (in/mm)	2.72 x 1.42 x 1.61 69 x 36 x 42
Weight without Mount (oz/g)	4.06 / 115
Weight with Mount (oz/g)	5.08 / 144

Maximum Caliber	1200 G
IP Standard (water rating)	IP67
Nitrogen Filled / Shockproof / Fog Proof	Yes / Yes / Yes
Lens Coating	Multicoated
Battery Life	Low: 80,000 Mid: 45,000 High: 1,600

FEATURES

- Shake Awake
- Unlimited Eye Relief
- IP67 Waterproof / Dustproof
- Fogproof / Shockproof
- 3 MOA Dot
- 9 Brightness Setting
- Aimpoint® T2 Footprint

INCLUDED ACCESSORIES

- Lens Cloth
- 2mm Hex Wrench
- T15 Torx Wrench
- CR2032 Battery
- Clear Flip-Up Lens Covers
- High Mount