



## **PORTABLE DIMENSIONS**

• 37" (.94 m) x 23" (.61 m) x 26" (.66 m)

#### **ENVIRONMENTAL DESIGN SPECIFICATIONS**

- Temp -20 C to +60 C (-4F to +140F)
- Relative Humidity 95% non-condensing

# INTELLIGENT

# USER FRIENDLY CONTROL PANEL WITH PROGRAMMABLE MEMORY

- Universal power adaptor/charger (Adaptor kit available for non-U.S.A. receptacles)
- Environmentally sealed keypad with security access control
- Brilliant LED bar graph indicates target strength
- Lighted LED displays M-Scope configuration
- Memory feature store settings for multiple operating environments
- Multi-mode traffic counter
- Adjustable volume control

# **DYNAMIC**

### **SINGLE-PERSON PORTABILITY**

- Assembles without tools in less than 5 minutes
- Weight: 83 lbs. (40 kilos) approximately
- Fully Portable: collapses onto its own compact wheeled carrier

# **EFFECTIVE**

### **HEAD-TO-TOE, ZONE SPECIFIC DETECTION**

• 3 sensor zones with brilliant LED detection indicators

#### **100 LEVELS OF ADJUSTABLE SENSITIVITY**

• Designed to meet your level of need

#### **DESIGNED FOR USE IN DEMANDING ENVIRONMENTS**

- Indoor or outdoor use (Not in inclement weather)
- Battery operated (Includes AC adapter & recharge kit)
- Operates approximately 40 hours on rechargeable batteries (Included)
- · Multiple units may work within close proximity to one another
- Designed to meet regulatory standards: NILECJ-0601.00

**U.S. PATENT 7,193,524** 

# Security Solutions FISHER LABS

TOLL FREE 1-800-685-5050 www.fisherlab.com • info@fisherlab.com 1120 Alza Drive, El Paso, TX 79907 U.S.A.

