

# Calonox 2 Sight



## THERMAL

Calonox 2 Sight offers true dual-purpose design. Handhold it for spotting and mount it your scope for shooting, in seconds, with no re-zeroing necessary. Built from all-European parts and featuring LIOTM technology in both Sight and View models, it offers a detection range of well over a mile and an identification range beyond 400 yards, bringing a new level of capability to the world of thermal optics.



## KEY FEATURES

- 640 x 840 Sensor, 12 micron Pixel, 60hz refresh
- No Re-zeroing
- LIO (icon already made)
- 1+ mile thermal detection range, 400+ yards identification range
- Shutterless
- Universal Clip-on
- App enhanced, remote control available

LIO	640 X 480 SENSOR	12 MICRON PIXEL	NO REZEROING	THERMAL COMPATIBLE
SHUTTERLESS DESIGN	UNIVERSAL MOUNTING	WIFI & BLUETOOTH	32GB	1+ MILE RANGE
400+ YARDS	HANDHELD VIEWING	WEAPON MOUNTED		

## INTENDED USE

- HUNTING
- OBSERVATION
- FINDING HOTSPOTS

## COLOR MODES



WHITE HOT



BLACK HOT



RAINBOW



RED HOT



GREEN HOT



RED FRAME

## LIVE VIEW



### LIVE VIEW

Calonox 2's Live View lets you stream its thermal image to a smartphone or tablet via the Leica2Hunt app, enabling a second person to monitor wildlife or control photo/video recording. The feature connects over Wi-Fi or Bluetooth for easy sharing and mobile management of recordings.

# Tech Specs

## CALONOX 2 SIGHT

### SPECS



Product Video

Designation	Calonox 2 Sight
Device type	Thermal imaging device
Order number	50511
Sensor type	VOx
Sensor size	640 x 480 px
Pixel size	12 µm
Screen type	OLED
Screen size, diagonal	0.49", active area 0.35"
Screen resolution	1280 x 960 px
Refresh rate	60 Hz
Lens focal length	42mm / 1.1
Thermal sensitivity NETD	< 40 mK
Optical magnification	1x
Digital zoom	1x / 2x temporary
Field of view	54' x 40.5' @ 100 yards
Diopter adjustment	no
Thermal range / resolution for subject 70" x 20"	
Aquisition range / Resolution	2,417 yards / 2 px
Detection range / Resolution	842 yards / 6 px
Identification range / Resolution	427 yards / 12 px
Adjustment reticle correction	Not necessary
Video recording / output	Yes, WiFi, USB-C
Video picture resolution	640 x 480 px
Cable socket	USB-C
Wireless connectivity	WiFi (2.4 Ghz) + BlueTooth
Internal memory	32 GB
Waterproof	IP67 / 1m for 30 minutes

### SPECS CONT.

Designation	Calonox 2 Sight
Operating temperature	-20 °C to +50 °C (-4°F to 122°F)
Operating temp. (charge battery)	+10 °C to +30 °C (50°F to 86°F)
Battery life	approx. 8 - 11 hours
Battery type	2x 2,420 mA/h not removable
Charging options	USB-C, household plug, power bank, car (cigarette lighter)
Accessory (eyepiece) thread	M43x0.75
Tripod thread	A ¼ DIN 4503 (¼"), M4 standard thread
Housing material	fiberglass-reinforced plastic with silicone armoring
Dimensions (L x W x H)	139 x 110 x 61 mm (5.5 x 4.3 x 2.4 in)
Shutter	shutterless
Weight (with battery)	approx. 650 g (22.9 oz)
Mounting	Rusan modular (direct to scope), Picatinny mount Leica part 59085
Recoil rating	up to .50 caliber

### MOUNT ADAPTERS SOLD SEPARATELY

Mount the Calonox 2 Sight on multiple riflescopes, allowing a seamless switch from handheld spotting to scope use.



Rusan Adapter



Rusan Adapter Ring



Picatinny Set

### INCLUDED IN THE KIT

Calonox 2 Sight, cordura case, charging cable, Tenebraex flip cap, rubber eyecup, carry strap, quick start guide, lens cleaning cloth, certificate.