# RifleScope Instruction

# READ CAREFULLY BEFORE YOU MOUNT YOUR SCOPE

A good quality mounting system is essential.

Be sure the mounting system is compatible with your guns scope conbination. In some cases it may be necessary to use extra high rings or extension rings.

Ask you local dealer to help you select a mounting system which will fit your needs.

. . . . . .

Before beginning the mounting procedure, be sure the gun action is open, clip or magazine is removed and a round is mot in the chamber. Do not attempt any work until the bun, has been cleared and determined to be safe.

Read the instructions supplied with the mounts first, then proceed. Follow the recommended procedure. Do not take short cuts, it may result in damage to the mounts or the gun.


#### FOCUSING THE EYE LENS

VTSTAA

- 1) Hold scope about three inches from your eye? A the best to produce the product of the product
- 2) Quickly glance through the scope at a featureless area such as a wall or the open sky used a tank but again to one of the control of the c


## CAUTION:DO NOT LOOK AT THE SUN AS PERMANENT EYE DAMAGE, EVEN BLINDNESS MAY RESULT

3) If the reticle did not instantly appear in sharp focus, loosen the eye bell locking ring, rotate the eye bell in either direction until reticle is sharply focused. (Note:some series do not have locking ring, rotate eyepiece to focus.)



#### ATTACHING SCOPE TO MOUNT

- 1) Remove ring caps from mount, place scope in cradle formed by uncapped rings.
- 2) Slide scope fore or aft to position scope at the proper eye point (full field of view can be seen).
- 3) Rotate scope to align the reticle horizontally and vertically hadring in the form
- 4) Replace ring caps and lighten firmly.




#### PRE-ZEROING

If available, use a bore sighting collimator to prezero your rifle!

At an approved range, or other safe area, bench rest the rifle. Remove the windage and elevation caps. If you have a bost action rifle, remove bolt. If you have a lever, pump or semi-auto loading rifle, use a mirror type bore sighting device, available from you firearm retailer.

If you have a zoom power scope, turn the power change ring to the highest setting. If your scope model is equipped with an adjustable objective lens for parallax correction, rotate the focusing ring to the appropriate setting.


- A) Sight through the bore at a target at 100 yards. More the rifle about to center the target in the bore.
- B) Sight through the scope and adjust the windage and elevaion screws to center the target on the reticle.





## FINAL - ZEROING

Since final zeroing involves live fire, check bore to be sure it is free of any obstructions before loading. Use eye and ear protection.



Fire three rounds at your target, note impact on target. Measure the distance from group center to target center. Adjust the windage and elevation screws accordingly. Each click adjustment will move the bullet impact by the amount shown on the dials at 100 yards.

Repace windage and elevation caps when zeroing is completed.





Each click of adjustment will move the bul-

let impact by the amount shown at the distance indicated

tance indicated:			
	50 YDS	100 YDS	200 YDS
TYPE	1/8"	1/4"	- 1/2 <sup>ii</sup>
A	176	1/4	172
TYPE	1/4"	1/2"	111
В	1/4	1/2	1

### MAINTAIINING YOUR SCOPE

Your riflescope is shockproof, waterproof and fogproof. You should never try to take it apart or clean it internally. If your scope rever does need repair or adjustments, it should be returned to you dealer. 85.

Your riflescope will perform it's best if occasionally wiped clean with a lens cloth or an optical lens paper like that for eyeglasses and camera lenses. Keep protective lens co vers in place when the scope is not being

Maintain the meatal surface of your scope by removing any dirt or sand with a soft brush to avoid scratching the finish. Wipe the scope with a damp cloth and follow with a dry cloth. Finally, wipe with asilicone treated cloth to restore luster and protect the scope against corrosion. Be carefull not to touch the lenses With the silicone cloth.

## FIREARM SAFETY DEPENDS ON YOU

- -Always keep the muzzle pointed in a safe
- -Firearms should be unloaded and locked when not actually in use.
- -Be sure of your target and what is beyond THEOL: MONTUM
- -Use correct ammuntion Always wear eye and ear protections when shooting. The Market Brown Co.
- -Be sure the barrel is clear of obstructions before shooting.
- -Learn the mechnical and handling charateristics of the firarm your are using.