



## 0340

### Protector

Cube Case

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the artic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- **Built-in, spring loaded pull handle**
- **Large 2-person fold down handles**
- **Stainless steel caster wheels included**
- **Watertight, crushproof, and dustproof**
- 3 level Pick N Pluck™ with convoluted lid foam
- Automatic Pressure Equalization Valve - balances interior pressure, keeps water out
- Easy open Double Throw latches
- Lifetime Guarantee of Excellence
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Stainless steel hardware and padlock protectors



## CONFIGURATIONS



**0340**  
Standard



**0344**  
With Padded Dividers



**0340NF**  
No Foam



**0340WF**  
With Foam

## DIMENSIONS

<b>Interior (L x W x D)</b>	18.00 x 18.00" x 18.00 (45.7 x 45.7 x 45.7 cm)
<b>Exterior (L x W x D)</b>	20.50 x 20.50" x 19.25 (52.1 x 52.1 x 48.9 cm)
<b>Lid Depth</b>	4.50" (11.4 cm)
<b>Bottom Depth</b>	13.50" (34.3 cm)
<b>Total Depth</b>	18" (45.7 cm)
<b>Int Volume</b>	3.38 ft³ (0.096 m³)

## MATERIALS

<b>Body</b>	Polypropylene
<b>Latch</b>	ABS
<b>O-Ring</b>	Polymer
<b>Pins</b>	Stainless Steel
<b>Foam</b>	1.3 lb Polyurethane

## Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311

### Purge Body

ABS

[sales@pelican.com](mailto:sales@pelican.com) • [www.pelican.com](http://www.pelican.com)

### Purge Vent

3 Micron Hydrophobic Non-Woven

*Document created on 05-16-19*

## COLORS

■ Black

■ OD Green

■ Desert Tan

## WEIGHT

<b>Weight With Foam</b>	29.76 lbs (13.5 kg)
<b>Weight Empty</b>	24.00 lbs (10.9 kg)
<b>Buoyancy</b>	220.46 lbs (100 kg)
<b>Master Pack Weight</b>	32.24 lbs (14.6 kg)

## TEMPERATURE

<b>Minimum Temperature</b>	-40°F (-40 °C)
<b>Maximum Temperature</b>	210°F (98.9 °C)

## CERTIFICATIONS

IP67  
Def Stan 81-41  
STANAG 4280

## FOAM PROPERTIES

<b>Layer 1 (Lid)</b>	1.00" Pad
<b>Layer 2 (Lid)</b>	3.00" Convolute
<b>Layer 3 (Base)</b>	1.00" Pad
<b>Layer 4 (Base)</b>	1.00" Pad
<b>Layer 5 (Base)</b>	3.84" Pick N Pluck
<b>Layer 6 (Base)</b>	3.84" Pick N Pluck
<b>Layer 7 (Base)</b>	3.84" Pick N Pluck

## OTHER

<b>Wheels</b>	2
<b>Master Pack</b>	1
<b>Nameplate</b>	yes
<b>Reduced Area</b>	yes
<b>Military</b>	yes

## ACCESSORIES