



## 1170 Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the artic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- **The hand-held electronics protection solution**
- **Watertight, crushproof, and dustproof**
- Automatic Pressure Equalization Valve - balances interior pressure, keeps water out
- Easy open Double Throw latches
- Lifetime Guarantee of Excellence
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Pick N Pluck™ with convoluted lid foam
- Stainless steel hardware



## CONFIGURATIONS



**1170**  
Standard



**1170NF**  
No Foam



**1170WF**  
With Foam

## DIMENSIONS

<b>Interior (L x W x D)</b>	10.54 x 6.04" x 3.16 (26.8 x 15.3 x 8 cm)
<b>Exterior (L x W x D)</b>	11.64 x 8.34" x 3.78 (29.6 x 21.2 x 9.6 cm)
<b>Lid Depth</b>	1.08" (2.7 cm)
<b>Bottom Depth</b>	2.08" (5.3 cm)
<b>Total Depth</b>	3.16" (8 cm)
<b>Int Volume</b>	0.12 ft <sup>3</sup> (0.003 m <sup>3</sup> )

## MATERIALS

<b>Body</b>	Polypropylene
<b>Latch</b>	ABS
<b>O-Ring</b>	Polymer
<b>Pins</b>	Stainless Steel
<b>Foam</b>	Polyurethane
<b>Purge Body</b>	ABS
<b>Purge Vent</b>	3 Micron Hydrophobic Non-Woven

## Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311

[sales@pelican.com](mailto:sales@pelican.com) • [www.pelican.com](http://www.pelican.com)

# COLORS

Document created on 05-20-19

■ Black

■ Silver

■ Orange

■ Yellow

■ OD Green

■ Desert Tan

# WEIGHT

<b>Weight With Foam</b>	2.10 lbs (1 kg)
<b>Weight Empty</b>	1.96 lbs (0.9 kg)
<b>Buoyancy</b>	7.25 lbs (3.3 kg)
<b>Master Pack Weight</b>	12.79 lbs (5.8 kg)

# TEMPERATURE

<b>Minimum Temperature</b>	-40°F (-40 °C)
<b>Maximum Temperature</b>	210°F (98.9 °C)

# CERTIFICATIONS

IP67

# FOAM PROPERTIES

<b>Layer 1 (Lid)</b>	1.10" Convolute
<b>Layer 2 (Base)</b>	0.50" Pad
<b>Layer 3 (Base)</b>	1.50" Pick N Pluck

# OTHER

<b>Master Pack</b>	6
--------------------	---

# ACCESSORIES