

#### 1430

#### **Protector**

Top Loader Case

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican  $^{\text{\tiny TM}}$  Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the artic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, overmolded rubber handles and stainless steel hardware.

#### • Unique top loading design

- 3 level Pick N Pluck™ with convoluted lid foam
- Automatic Pressure Equalization Valve balances interior pressure, keeps water out
- Comfortable rubber over-molded handle
- Easy open Double Throw latches
- · Lifetime Guarantee of Excellence
- O-ring sea
- Open cell core with solid wall design strong, light weight
- Stainless steel hardware and padlock protectors



## **CONFIGURATIONS**



1430 Standard



With Padded Dividers & Lid Organizer



**1437**With Padded Office Divider Set & Lid Organizer



1430NF No Foam



1430WF With Foam

## **DIMENSIONS**

Interior (L x W x D) 13.56 x 5.76" x 11.70 (34.4 x 14.6 x 29.7 cm) Exterior (L x W x D) 16.40 x 8.71" x 13.15 (41.7 x 22.1 x 33.4 cm)

 Lid Depth
 2.00" (5.1 cm)

 Bottom Depth
 9.70" (24.6 cm)

 Total Depth
 11.7" (29.7 cm)

 Int Volume
 0.53 ft³ (0.015 m³)

## **MATERIALS**

**Body** Polypropylene

LatchABSO-RingPolymerPinsStainless SteelFoam1.3 lb Polyurethane

Purge Body ABS

Purge Vent 3 Micron Hydrophobic Non-Woven

#### **Pelican**

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311

sales@pelican.com • www.pelican.com

#### **COLORS**

**WEIGHT** 

Document created on 05-20-19

OD Green

Desert Tan

Yellow

Black

Weight With Foam

6.50 lbs (2.9 kg)

Orange

 Weight Empty
 5.60 lbs (2.5 kg)

 Buoyancy
 59.00 lbs (26.8 kg)

 Master Pack Weight
 8.09 lbs (3.7 kg)

# **TEMPERATURE**

Minimum Temperature -40°F (-40 °C)

Maximum Temperature 210°F (98.9 °C)

## **CERTIFICATIONS**

IP67

Def Stan 81-41 STANAG 4280

# FOAM PROPERTIES

Layer 1 (Lid)2.00" Convolute

**Layer 2 (Base)** 1.00" Pad

Layer 3 (Base)2.87" Pick N PluckLayer 4 (Base)2.78" Pick N PluckLayer 5 (Base)2.78" Pick N Pluck

# **OTHER**

Master Pack1NameplateyesMilitaryyes

# **ACCESSORIES**