

1460

Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the artic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, overmolded rubber handles and stainless steel hardware.

- Also available with EMS Organizer and Dividers
- Personalized nameplate service available
- Top lid opens up to 180° for on-the-field anti-roll stability when open
- · Watertight, crushproof, and dustproof
- Automatic Pressure Equalization Valve balances interior pressure, keeps water out
- Comfortable rubber over-molded handles
- Easy open Double Throw latches
- · Lifetime Guarantee of Excellence
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Stainless steel hardware and padlock protectors



CONFIGURATIONS



1460 Standard



1460AALGWith Custom Foam for 9430 / 9435



1460NF No Foam



1460WF With Foam

DIMENSIONS

Interior (L x W x D) 18.54 x 9.92" x 10.92 (47.1 x 25.2 x 27.7 cm) Exterior (L x W x D) 20.85 x 12.73" x 12.75 (53 x 32.3 x 32.4 cm)

 Lid Depth
 4.91" (12.5 cm)

 Bottom Depth
 6.01" (15.3 cm)

 Total Depth
 10.92" (27.7 cm)

 Int Volume
 1.16 ft³ (0.033 m³)

MATERIALS

Body Polypropylene

Latch EXL
O-Ring Polymer
Pins Stainless Steel
Foam Polyurethane

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311

sales@pelican.com • www.pelican.com **Purge Body**

3 Micron Hydrophobic Non-Woven Document created on 05-20-19 **Purge Vent**

COLORS

Black OD Green Desert Tan

WEIGHT

Weight With Foam 12.48 lbs (5.7 kg) **Weight Empty** 8.75 lbs (4 kg) **Buoyancy** 82.00 lbs (37.2 kg)

TEMPERATURE

Minimum Temperature -40°F (-40 °C) Maximum Temperature 210°F (98.9 °C)

CERTIFICATIONS

IP67

FOAM PROPERTIES

Layer 1 (Lid) 1.60" Pick N Pluck 1.38" Pick N Pluck Layer 2 (Base) Layer 3 (Base) 2.20" Pick N Pluck Layer 4 (Base) 2.20" Pick N Pluck Layer 5 (Base) 2.20" Pick N Pluck Layer 6 (Base) 2.20" Pick N Pluck

OTHER

Military yes

ACCESSORIES