



1600 Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the artic or the heat of battle, Pelican cases have survived. Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- Personalized nameplate service available
- **Watertight, crushproof, and dustproof**
- 2 level Pick N Pluck™ with convoluted lid foam
- Automatic Pressure Equalization Valve - balances interior pressure, keeps water out
- Comfortable rubber over-molded handle
- Lifetime Guarantee of Excellence
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Stainless steel hardware and padlock protectors



CONFIGURATIONS



1600
Standard



1604
With Padded Dividers



1600NF
No Foam



1600TP
With TrekPak Divider System



1600WF
With Foam

DIMENSIONS

Interior (L x W x D)	21.51 x 16.54" x 7.99 (54.6 x 42 x 20.3 cm)
Exterior (L x W x D)	24.39 x 19.36" x 8.79 (62 x 49.2 x 22.3 cm)
Lid Depth	1.75" (4.4 cm)
Bottom Depth	6.12" (15.5 cm)
Total Depth	7.87" (20 cm)
Int Volume	1.65 ft³ (0.047 m³)

MATERIALS

Body	Polypropylene
Latch	ABS
O-Ring	Polymer
Pins	Stainless Steel
Foam	1.3 lb Polyurethane
Purge Body	ABS
Purge Vent	3 Micron Hydrophobic Non-Woven

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311

sales@pelican.com • www.pelican.com

COLORS

Document created on 05-29-19

■ Black

■ Silver

■ Orange

■ Yellow

■ OD Green

■ Desert Tan

WEIGHT

Weight With Foam	14.11 lbs (6.4 kg)
Weight Empty	13.00 lbs (5.9 kg)
Buoyancy	117.00 lbs (53.1 kg)
Master Pack Weight	34.75 lbs (15.8 kg)

TEMPERATURE

Minimum Temperature	-40°F (-40 °C)
Maximum Temperature	210°F (98.9 °C)

CERTIFICATIONS

IP67
MIL C-4150J
Def Stan 81-41
STANAG 4280
ATA 300

FOAM PROPERTIES

Layer 1 (Lid)	2.00" Convolute
Layer 2 (Base)	1.00" Pad
Layer 3 (Base)	2.38" Pick N Pluck
Layer 4 (Base)	2.38" Pick N Pluck

OTHER

Master Pack	2
Nameplate	yes
Military	yes

ACCESSORIES