



# 1630

## Protector

Transport Case

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the artic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- Personalized nameplate service available
- **4 strong polyurethane wheels with stainless steel bearings (wheel diameter is 5.3cm)**
- **Watertight, crushproof, and dustproof**
- 3 level Pick N Pluck™ with convoluted lid foam
- Automatic Pressure Equalization Valve - balances interior pressure, keeps water out
- Easy open Double Throw latches
- Fold down handles
- Lifetime Guarantee of Excellence
- Note: Please consult a sales specialist for more details.
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Reinforced corners
- Retractable extension handle
- Stackable
- Stainless steel padlock protectors



## CONFIGURATIONS



**1630**  
Standard



**1634**  
With Padded Dividers



**1630NF**  
No Foam



**1630WF**  
With Foam

## DIMENSIONS

<b>Interior (L x W x D)</b>	27.70 x 20.98" x 15.50 (70.4 x 53.3 x 39.4 cm)
<b>Exterior (L x W x D)</b>	31.28 x 24.21" x 17.48 (79.5 x 61.5 x 44.4 cm)
<b>Lid Depth</b>	3.25" (8.3 cm)
<b>Bottom Depth</b>	12.14" (30.8 cm)
<b>Total Depth</b>	15.39" (39.1 cm)
<b>Int Volume</b>	5.21 ft <sup>3</sup> (0.148 m <sup>3</sup> )

## Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311

[sales@pelican.com](mailto:sales@pelican.com) • [www.pelican.com](http://www.pelican.com)

# MATERIALS

Document created on 05-22-19

<b>Body</b>	Polypropylene
<b>Latch</b>	ABS
<b>O-Ring</b>	Polymer
<b>Pins</b>	Stainless Steel
<b>Foam</b>	1.3 lb Polyurethane
<b>Purge Body</b>	ABS
<b>Purge Vent</b>	3 Micron Hydrophobic Non-Woven

# COLORS

 Black	 OD Green	 Desert Tan
---	--	--

# WEIGHT

<b>Weight With Foam</b>	36.00 lbs (16.3 kg)
<b>Weight Empty</b>	31.00 lbs (14.1 kg)
<b>Buoyancy</b>	350.00 lbs (158.8 kg)
<b>Master Pack Weight</b>	42.00 lbs (19.1 kg)

# TEMPERATURE

<b>Minimum Temperature</b>	-40°F (-40 °C)
<b>Maximum Temperature</b>	210°F (98.9 °C)

# CERTIFICATIONS

IP67  
Def Stan 81-41  
STANAG 4280

# FOAM PROPERTIES

<b>Layer 1 (Lid)</b>	3.20" Pad
<b>Layer 2 (Base)</b>	1.00" Pad
<b>Layer 3 (Base)</b>	3.75" Pick N Pluck
<b>Layer 4 (Base)</b>	3.75" Pick N Pluck
<b>Layer 5 (Base)</b>	3.75" Pick N Pluck

# OTHER

<b>Wheels</b>	4
<b>Extendable Handle</b>	yes
<b>Master Pack</b>	1
<b>Nameplate</b>	yes
<b>Reduced Area</b>	yes

# ACCESSORIES