

#### 1670

#### **Protector**

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the artic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, overmolded rubber handles and stainless steel hardware.

- Personalized nameplate service available
- 4 strong polyurethane wheels with stainless steel bearings
- Watertight, crushproof, and dustproof
- 2 level Pick N Pluck™ with convoluted lid foam
- Automatic Pressure Equalization Valve balances interior pressure, keeps water out
- Easy open Double Throw latches
- Lifetime Guarantee of Excellence
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Retractable extension handle
- Stainless steel hardware and padlock protectors
- Two oversized fold down handles for extra grip



# **CONFIGURATIONS**



**1670** Standard



1670NF No Foam



**1670WF** With Foam



**1674** With Padded Dividers

## **DIMENSIONS**

Interior (L x W x D) 28.10 x 16.49" x 9.19 (71.4 x 41.9 x 23.3 cm) Exterior (L x W x D) 31.04 x 19.39" x 11.17 (78.8 x 49.3 x 28.4 cm)

 Lid Depth
 1.80" (4.6 cm)

 Bottom Depth
 7.39" (18.8 cm)

 Total Depth
 9.19" (23.3 cm)

 Int Volume
 2.46 ft³ (0.07 m³)

## **MATERIALS**

**Body** Polypropylene

Latch ABS
O-Ring Polymer
Pins Stainless Steel
Foam 1.3 lb Polyurethane

#### **Pelican**

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311

 $\underline{sales@pelican.com} \bullet \underline{www.pelican.com}$ **Purge Body** 

3 Micron Hydrophobic Non-Woven Document created on 05-28-19 **Purge Vent** 

# **COLORS**



## **WEIGHT**

Weight With Foam 26.00 lbs (11.8 kg) **Weight Empty** 23.00 lbs (10.4 kg) **Buoyancy** 182.00 lbs (82.6 kg) **Master Pack Weight** 49.00 lbs (22.2 kg)

# **TEMPERATURE**

**Minimum Temperature** -40°F (-40 °C) **Maximum Temperature** 210°F (98.9 °C)

#### OTHER

Wheels 4 1 **Master Pack** 

# **ACCESSORIES**