



1730

Protector

Transport Case

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the artic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- Personalized nameplate service available
- **The following custom features require a 100 pc. minimum order**
- **Extra deep stackable cleats**
- **Strong polyurethane wheels with stainless steel bearings**
- **Watertight, crushproof, and dustproof**
- 5-piece foam set
- Automatic Pressure Equalization Valve - balances interior pressure, keeps water out
- Easy open Double Throw latches
- Fold down handles
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Optional Humidity gauge changes color above 40%
- Optional Manual Pressure Equalization Valve
- Stainless steel hardware and padlock protectors



CONFIGURATIONS



1730
Standard



1730NF
No Foam



1730WF
With Foam

DIMENSIONS

Interior (L x W x D)	34.00 x 24.00" x 12.50 (86.4 x 61 x 31.8 cm)
Exterior (L x W x D)	37.50 x 27.13" x 14.37 (95.3 x 68.9 x 36.5 cm)
Lid Depth	2.50" (6.4 cm)
Bottom Depth	10.00" (25.4 cm)
Total Depth	12.5" (31.8 cm)
Int Volume	5.9 ft³ (0.167 m³)

MATERIALS

Body	Polypropylene
Latch	ABS
O-Ring	Polymer

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311

Pins	Stainless Steel	sales@pelican.com • www.pelican.com
Foam	1.3 lb Polyurethane	
Purge Body	ABS	<i>Document created on 05-22-19</i>
Purge Vent	3 Micron Hydrophobic Non-Woven	

COLORS

 Black	 OD Green	 Desert Tan
---	--	--

WEIGHT

Weight With Foam	38.00 lbs (17.2 kg)
Weight Empty	30.00 lbs (13.6 kg)
Buoyancy	416.00 lbs (188.7 kg)
Master Pack Weight	43.00 lbs (19.5 kg)

TEMPERATURE

Minimum Temperature	-40°F (-40 °C)
Maximum Temperature	210°F (98.9 °C)

CERTIFICATIONS

IP67

FOAM PROPERTIES

Layer 1 (Lid)	2.50" Convolute
Layer 2 (Base)	1.00" Pad
Layer 3 (Base)	2.94" Pick N Pluck
Layer 4 (Base)	2.94" Pick N Pluck
Layer 5 (Base)	2.94" Pick N Pluck

OTHER

Wheels	2
Master Pack	1
Nameplate	yes

ACCESSORIES