



## iM2370

### Storm

Laptop Case

The Pelican™ Storm Case™ has the same legendary DNA as our Pelican Protector Case, with one primary difference: A unique Press and Pull latch that locks automatically, but open with a light touch.

Guaranteed for life, the Pelican Storm case is made in the USA and engineered using the finest components.

- Guaranteed for life
- **Watertight, crushproof, and dustproof**
- Two Press & Pull Latches
- Two Padlockable Hasps
- Double-layered, Soft-grip Handle
- Vortex™ Valve
- Powerful Hinges
- Lightweight Strong HPX® Resin



## CONFIGURATIONS



**iM2370**  
Standard



**iM2370-X0000**  
No Foam



**iM2370-X0002**  
With Padded Dividers



**iM2370-X0003**  
Computer Case Deluxe



**iM2370-X0001**  
With Foam

## DIMENSIONS

<b>Interior (L x W x D)</b>	18.20 x 12.10" x 5.20 (46.2 x 30.7 x 13.2 cm)
<b>Exterior (L x W x D)</b>	20.00 x 14.70" x 5.80 (50.8 x 37.3 x 14.7 cm)
<b>Lid Depth</b>	1.70" (4.3 cm)
<b>Bottom Depth</b>	3.50" (8.9 cm)
<b>Total Depth</b>	5.2" (13.2 cm)
<b>Int Volume</b>	0.66 ft <sup>3</sup> (0.019 m <sup>3</sup> )

## MATERIALS

<b>Body</b>	Injection Molded HPX™ high performance resin
<b>Latch</b>	Valox - Polybutylene Terephthalate (PBT)
<b>Latch (Alt)</b>	Xenoy - Polyester/Polycarbonate blend
<b>O-Ring</b>	EPDM
<b>Pins</b>	Stainless Steel
<b>Pins (Alt)</b>	Aluminum
<b>Foam</b>	1.3/1.35 polyester
<b>Purge Body</b>	Valox - Polybutylene Terephthalate (PBT)
<b>Purge Body (Alt)</b>	Xenoy - Polyester/Polycarbonate blend
<b>Purge Vent</b>	Gortex membrane

**Pelican**

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311

[sales@pelican.com](mailto:sales@pelican.com) • [www.pelican.com](http://www.pelican.com)

# COLORS

Document created on 05-23-19

■ Black

■ OD Green

# WEIGHT

<b>Weight With Foam</b>	7.20 lbs (3.3 kg)
<b>Weight Empty</b>	5.70 lbs (2.6 kg)
<b>Buoyancy</b>	43.64 lbs (19.8 kg)
<b>Master Pack Weight</b>	29.00 lbs (13.2 kg)

# TEMPERATURE

<b>Minimum Temperature</b>	-20°F (-28.9 °C)
<b>Maximum Temperature</b>	140°F (60 °C)

# CERTIFICATIONS

MIL-STD-810F  
ATA 300  
FED-STD-101C

# FOAM PROPERTIES

<b>Layer 1 (Lid)</b>	1.58" Convolute
<b>Layer 2 (Base)</b>	0.50" Pad
<b>Layer 3 (Base)</b>	1.44" Pick N Pluck
<b>Layer 4 (Base)</b>	1.44" Pick N Pluck

# OTHER

<b>Master Pack</b>	4
<b>Military</b>	yes

# ACCESSORIES