



iM2400

Storm

Laptop Case

The Pelican™ Storm Case™ has the same legendary DNA as our Pelican Protector Case, with one primary difference: A unique Press and Pull latch that locks automatically, but open with a light touch. Guaranteed for life, the Pelican Storm case is made in the USA and engineered using the finest components.

- Guaranteed for life
- **Watertight, crushproof, and dustproof**
- Two Press & Pull Latches
- Two Padlockable Hasps
- Double-layered, Soft-grip Handle
- Vortex™ Valve
- Powerful Hinges
- Lightweight Strong HPX® Resin



CONFIGURATIONS



iM2400
Standard



iM2400-X0000
No Foam



iM2400-X0002
With Padded Dividers



iM2400-X0001
With Foam

DIMENSIONS

Interior (L x W x D)	18.00 x 13.00" x 6.70 (45.7 x 33 x 17 cm)
Exterior (L x W x D)	19.20 x 15.20" x 7.30 (48.8 x 38.6 x 18.5 cm)
Lid Depth	2.00" (5.1 cm)
Bottom Depth	4.70" (11.9 cm)
Total Depth	6.7" (17 cm)
Int Volume	0.91 ft ³ (0.026 m ³)

MATERIALS

Body	Injection Molded HPX™ high performance resin
Latch	Valox - Polybutylene Terephthalate (PBT)
Latch (Alt)	Xenoy - Polyester/Polycarbonate blend
O-Ring	EPDM
Pins	Stainless Steel
Pins (Alt)	Aluminum
Foam	1.3/1.35 polyester
Purge Body	Valox - Polybutylene Terephthalate (PBT)
Purge Body (Alt)	Xenoy - Polyester/Polycarbonate blend
Purge Vent	Gortex membrane

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311

sales@pelican.com • www.pelican.com

COLORS

Document created on 05-23-19

■ Black

■ Yellow

■ OD Green

WEIGHT

Weight With Foam	7.80 lbs (3.5 kg)
Weight Empty	6.50 lbs (2.9 kg)
Buoyancy	59.02 lbs (26.8 kg)
Master Pack Weight	28.30 lbs (12.8 kg)

TEMPERATURE

Minimum Temperature	-20°F (-28.9 °C)
Maximum Temperature	140°F (60 °C)

CERTIFICATIONS

MIL-STD-810F
ATA 300
FED-STD-101C

FOAM PROPERTIES

Layer 1 (Lid)	2.00" Convolute
Layer 2 (Base)	0.63" Pad
Layer 3 (Base)	2.12" Pick N Pluck
Layer 4 (Base)	2.12" Pick N Pluck

OTHER

Master Pack	3
Military	yes

ACCESSORIES