



ELECTRO-OPTICS - RED DOT

# ROMEO-X SIG-LOC™ PRO

FULLY ENCLOSED REFLEX SIGHT, FOR FULL SIZE SIG-LOC™ PISTOLS

## ROMEO-X SIG-LOC™ PRO

FULLY ENCLOSED REFLEX SIGHT, FOR  
FULL SIZE SIG-LOC PISTOL

SORX1500 | SORX1530 | SORX1560

- ▶ A fully enclosed, sealed and purged optical system, for ultimate protection from the elements
- ▶ Mounts from underneath the pistol slide, utilizing the SIG-LOC™ mounting system, for the strongest lockup in the industry
- ▶ 7075 Aluminum housing with machined anti-reflection grooves on all rear surfaces for reduced glare
- ▶ Extremely low deck height, allowing a full sight picture and co-witness with standard-height sights
- ▶ A high-efficiency point source LED emitter, available in Circle/Dot, 3 MOA, or 6 MOA reticle configurations
- ▶ Independent brightness adjustment buttons that are recessed within a protective plate. Buttons have bump features above UP and below DOWN, so they can be determined by feel
- ▶ 15 brightness settings, with 3 of the settings optimized for use with Gen 3+ NV devices
- ▶ A side-mounted CR2032 battery compartment with a threaded battery cap, for easy battery changes without the need to remove the optic from the firearm
- ▶ Minimum continuous runtime of 20,000 hours, at medium brightness setting
- ▶ MOTAC (Motion Activated Illumination)
- ▶ MAGNETAC (Magnetic Activation)
- ▶ D.A.R.C. (Dark Adaptive Reticles & Coatings)
- ▶ Designed, developed, tested and assembled in the USA



A fully enclosed, sealed and purged optical system, for ultimate protection from the elements



Mounts from underneath the pistol slide, utilizing the SIG-LOC™ mounting system, for the strongest lockup in the industry



7075 Aluminum housing

SKU#:

SORX1500 | SORX1530 | SORX1560

UPC:

798681715855 | 798681715862 | 798681715879



ELECTRO-OPTICS - RED DOT

# ROMEO-X SIG-LOC™ PRO

FULLY ENCLOSED REFLEX SIGHT, FOR FULL SIZE SIG-LOC™ PISTOLS

PRODUCT DETAILS			
SKU#	SORX1500	SORX1530	SORX1560
HOUSING MATERIAL	7075 ALUMINUM		
HOUSING FINISH	BLACK CERAKOTE		
CLEAR APERTURE DIAMETER (MEASURED DIAGONALLY)	24 MM		
LENS MATERIAL	GLASS		
LENS TYPE	ASPHERE		
BATTERY TYPE	CR2032		
BATTERY LOCATION	SIDE		
BATTERY ACCESS	SLOTTED THREADED CAP		
BATTERY LIFE IN HOURS AT MEDIUM SETTING	UP TO 20,000 (DOT ONLY)		
EMITTER TYPE	SINGLE HIGH EFFICIENCY POINT SOURCE LED		
WINDAGE ADJUSTMENT RANGE	80 MOA		
ELEVATION ADJUSTMENT RANGE	40 MOA		
ADJUSTMENT RESOLUTION PER CLICK	1.5 MOA		
ADJUSTMENT SCREW TYPE	SLOTTED HEAD		
TACTILE ADJUSTMENT DETENTS (CLICKS)	YES		
BRIGHTNESS ADJUSTMENT SETTINGS	15 (12 DAY, 3NV)		
RETICLE OPTIONS	RED CIRCLE/DOT (2 MOA)	3 MOA RED DOT	6 MOA RED DOT
WATER RESISTANCE	IPX-8		
DROP RATING	3 DROPS, FROM 5 FEET (ONTO CONCRETE, MOUNTED TO 42-OUNCE WEIGHT)		
MOUNTING FOOTPRINT	SIG-LOC™ PRO		
MEASUREMENTS	IMPERIAL	METRIC	
OVERALL LENGTH	1.9 in	48.26 mm	
OVERALL HEIGHT	.96 in	24.38 mm	
OVERALL WIDTH	1.24 in	31.50 mm	
WEIGHT WITH BATTERY	1.46 oz	41.39 g	

COMPATIBLE WITH NEW P320  
AND SOME NEW CLASSIC LINE  
PISTOLS WITH THE SIG-LOC  
PRO FOOTPRINT.



**SIGSAUER®**