



ELECTRO-OPTICS - RED DOT

ROME09T 1x38 mm

MIL-SPEC DUAL DOT SIGHT



Dual (Red and Green) independently zeroed emitters.



Designed and tuned for passive NV performance, including NV Override Control.



Proprietary optical design mitigates downrange light signature.

ROME09T

RIFLE RED DOT SIGHT

SOR91001 - BLACK / SOR91002 - FDE

- ▶ Dual (Red and Green) independently zeroed emitters.
- ▶ Designed and tuned for passive NV performance, including NV Override Control
- ▶ Proprietary optical design mitigates downrange light signature.
- ▶ 50,000 hour runtime and 10 hour reserve without battery.
- ▶ Titanium shroud and mounting hardware
- ▶ IPX8 Waterproof and fog-proof performance (2 ATM for 2 Hours)
- ▶ Tested to MIL-810-STD
- ▶ Assembled in the USA
- ▶ Use cases for dual aiming points:
 - Changes in ammo such as 300 Blackout Supersonic and Subsonic
 - Caliber Exchange Kits
 - Suppressed and Unsuppressed
 - Different Zero Distances
 - Standard Zero and CQB Zero

SKU#:

SOR91001 - BLACK / SOR91002 - FDE

UPC:

798681624843 / 798681625918



ELECTRO-OPTICS - RED DOT

ROME09T 1x38 mm

MIL-SPEC DUAL DOT SIGHT

PRODUCT DETAILS		
SKU#	SOR91001 - BLACK / SOR91002 - FDE	
MAGNIFICATION	1x	
OBJECTIVE LENS DIAMETER (MM)	38mm	
OPTIC LENS COATINGS	DUAL NOTCH, ANTI-REFLECTIVE, SCRATCH RESISTANT, HYDROPHOBIC	
LIGHT TRANSMISSION DOWNRANGE	NONE	
RED EMITTER	1 MOA DOT WITH USER SELECTABLE 65 MOA CIRCLE	
GREEN EMITTER	2.5 MOA DOT	
ILLUMINATION SETTINGS	15 TOTAL - 12 DAY TIME AND 3 NV	
BATTERY TYPE	CR123	
ON-BOARD RESERVE CELL IN HOURS	10	
TOTAL TRAVEL	100 MOA	
RUN TIME IN HOURS	50,000	
ADJUSTMENT	0.5 MOA PER CLICK	
SIGHT HEIGHT	1.63 IN	
WATER PROOF RATING	IPX-8 (2 ATM FOR 2 HOURS)	
MEASUREMENTS	IMPERIAL	METRIC
OVERALL LENGTH	4.2 in	107 mm
OVERALL HEIGHT	2.9 in	73 mm
OVERALL WIDTH	2.4 in	61 mm
WEIGHT W/O BATTERY	13.1 oz	371 g
WEIGHT W/ BATTERY	13.7 oz	388 g

ACCESSORIES:



Accessories include:
Flipback lens caps, lenspen, multitool,
and Killflash (ARD).



SIGSAUER®