



LENS REMOVAL



To separate the lens from the frame grasp the brow bar indicated in the drawing and pull apart.

NOSE PIECE REMOVAL*

1) The nose piece and primary lens are interlocking.




2) To detach pull a leg of the nose piece. Once the leg is disengaged the nose piece will simply rotate out.




*Should you require corrective lenses remove the rx carrier prior to removing the nosepiece. See Rx Carrier instruction

INSTALLING THE LENS - STEP 1



Position the slot of the brow bar to the notch of the lens...

INSTALLING THE LENS - STEP 2



... and squeeze together as pictured

MAINTENANCE: Wiley X lenses are specially coated to offer superior abrasion resistance. Please follow below instructions to prolong the life of your lenses and keep them performing at their best:

- Clean lenses with water only.
- Do not use solvents or special cleaners.
- Use micro-fiber cleaning cloth provided to gently wipe clean.
- Never use paper products to clean and avoid wiping lens surface when dry and/or dirty as this may potentially scratch the lens.

WARNING: Wiley X brand eyewear is tested tough. However, impact resistant eyewear is not unbreakable and does not provide unlimited eye protection under all circumstances and conditions. Misused, abused, scratched and/or damaged eyewear can reduce impact protection (and void your limited warranty). Dirty and/or wet eyewear can impair vision and reduce safety (resulting in personal injury and/or property damage). Keep your Wiley X eyewear clean with water only. Do not use solvents or abrasives as it could scratch or damage the product reducing its effectiveness. Store your Wiley X eyewear in the protective case provided to prolong the life of the lenses. Most of all, take all appropriate precautions when wearing your Wiley X eyewear during hazardous and/or dangerous activities and conditions. Wiley X, Inc. is not responsible for personal injury, property damage or losses incurred while using Wiley X brand products.



SABER INSTRUCTIONS




WILEY X INC: 1.800.776.7842 // 925.243.9810 // WILEYX.COM
7800 PATTERSON PASS ROAD, LIVERMORE CA 94550 USA
WILEY X EUROPE LLC: +45 96 93 00 45 // WILEYX.EU
SØNDERGADE 8-10 7570 VEMB DENMARK

ICSA8BER[0]

COPYRIGHT © 2014 WILEY X, INC. ALL RIGHTS RESERVED.


WILEY X, WX, BLACK OPS, logos, tag lines and product names are trademarks or registered trademarks (marcas registradas) of Wiley X, Inc. in the U.S. and other countries. Logos © 2007-2014 Wiley X, Inc. All rights reserved.

INSTALLING NOSE PIECE




To install the nose piece, simply align the slot of the nosepiece with the lens and squeeze together.

NOSE PADS ADJUSTMENT




The wire core nose pads are adjustable ensuring the best fit for you.

INSTALLING THE PRESCRIPTION CARRIER - STEP 1




The prescription carrier is held in place by aligning the buds on the Rx carrier into the notches on the nose piece.

INSTALLING THE PRESCRIPTION CARRIER - STEP 2




Align the groove of the nose piece into the center notch of the frame.

INSTALLING THE PRESCRIPTION CARRIER - STEP 3



Position hands as pictured above and squeeze together until the nose piece completely seats into the lens.

TEMPLES / TACTICAL STRAP



TEMPLE ADJUSTMENT

The length of the temple arm may be adjusted by up to .75" with the 4 position extendable arm.

INSTALLING TACTICAL STRAP

Pull the adjustable temple arm so it is separated from the frame. Replace with tactical strap connectors, pushing firmly until they click.