


# 3-9x40 mm Riflescope



Winchester® Supreme®  
Wire Reticle

## Key Features

- » Fully multi-coated lenses throughout the optical system.
- » Excellent low light performance.
- » Beryllium bronze springs.
- » One-piece housing machined from tough A6063-T6 aluminum.
- » Black anodized aluminum exterior.
- » Designed to stand up to 800 Gs of recoil for standard & magnum rifles, and muzzleloaders.
- » Nitrogen filled and sealed optical system for fog and water.
- » Smooth fast focus eyepiece adjustment.
- » Knurled power adjustment ring and turret knobs for a secure grip.
- » Fingertip turret adjustment for windage and elevation.
- » Zero reset turrets can quickly be adjusted back to zero with a screwdriver or coin.
- » Lens cover, cleaning cloth, and user manual.

Winchester Supreme quality and performance at the range and in the field ensures you have a dependable optic to trust on your favorite rifle, for your next great adventure on paper or game.

Premium lenses transmit the maximum amount of light to your eye through our Winchester WINcoat™ multicoating. This coating not only reduces harsh glare but carries accurate color while providing a durable scratch resistant coating to exterior lens surfaces.

Winchester Supreme riflescopes utilize Second Focal Plane (SFP) reticles. This means that the reticle stays the same size throughout the scope's magnification range, while only the image changes size. This allows for the most precise shot placement at any distance, and the reticle will always have the same appearance.

WINCHESTER® SUPREME® RIFLESCOPE	3-9x40 mm
MAGNIFICATION RANGE	3X-9X
OBJECTIVE LENS DIAMETER	42 mm
OBJECTIVE OUTSIDE DIAMETER	47.5 mm
OCULAR LENS DIAMETER	35.5 mm
OCULAR OUTSIDE DIAMETER	44 mm
BODY TUBE DIAMETER	1"
LENGTH	313 mm
	12.3 in
WEIGHT	501.5 g
	17.5 oz
CONSTRUCTION MATERIAL	A6063-T6
BODY CONSTRUCTION	1 Piece
COLOR / FINISH	Black Matte
WATERPROOF	YES
FOGPROOF	YES
SHOCKPROOF	YES
SIDE FOCUS	NA
PARALLAX ADJUSTMENT	NA
PARALLAX ADJUSTMENT RANGE	NA
PARALLAX SETTING	100 y
ADJUSTMENT TURRET TYPE	Low Turret-Finger Adjustable
WINDAGE ADJUSTMENT RANGE	90 MOA
HORIZONTAL EFFECTIVE RANGE	±35 MOA
ELEVATION ADJUSTMENT RANGE	90 MOA
EFFECTIVE VERTICAL ADJUSTMENT RANGE	±35 MOA
CLICK VALUE	0.25 MOA
RETICLE TYPE (ETCHED / WIRE)	Wire
RETICLE DESIGN	Plex
EYE RELIEF	120-98 mm
	5.2-4.1 in
EXIT PUPIL	13.33 mm - 4.44 mm
FIELD OF VIEW (FOV) @ 100 YARDS	38.4 ft - 12.8 ft
FOCAL PLANE	Second (SFP)
DIOPTER COMPENSATION	+2/-2.5
ZERO STOP	NO
THREADED FOR SUNSHADE	NO
RESETTABLE TURRET	YES
IP RATING	IPX7 (1m/30min)
FULL MULTICOAT TYPE	Winchester WINcoat™